


# SHINWA EXPRESS *Application*

VOL. 231

## Analysis of Peptide standards using the ULTRON AF-HILIC-CD



Column: ULTRON AF-HILIC-CD (2  $\mu$ m)  
 Column size: 150 mmL x 2.0 mm I.D.  
 Mobile phase: 10 mM HCO<sub>2</sub>NH<sub>4</sub> (pH 3.0)/CH<sub>3</sub>CN = 30/70  
 Flow rate: 0.26 mL/min  
 Column temp.: 40°C  
 Detection: UV-200 nm

Sample: 1. Val-Tyr-Val (0.1 mg/mL)  
 2. Leucine Enkephalin (0.1 mg/mL)  
 3. Methionine Enkephalin (0.1 mg/mL)  
 4. Gly-Tyr (0.1 mg/mL)  
 Diluent: 50% acetonitrile  
 Injection vol.: 2  $\mu$ L

### ● Features of the ULTRON AF-HILIC-CD

1. ULTRON AF-HILIC-CD is a HILIC column in which  $\beta$ -cyclodextrin is chemically bonded to a silica gel via a spacer.
2. The column has high selectivity for molecular structure.
3. The column shows high resolution analysis for structural analogues and structural isomers.
4. The column is suitable for sugar analysis by suppressing schiff base formation and anomer separation.



**SHINWA CHEMICAL INDUSTRIES LTD.**

50-2 Kagekatsu-cho, Fushimi-ku  
 Kyoto 612-8307 Japan  
 TEL: +81-75-621-2360 FAX: +81-75-602-2660  
 E-mail: info@shinwa-cpc.co.jp  
 Website: <https://shinwa-cpc.co.jp/en/>

## ■ Analytical column specifications ■

### ULTRON AF-HILIC-CD

Product name	Particle size (μm)	Column dimensions Length x I.D. (mm)
ULTRON AF-HILIC-CD	2	50×2.0
		50×3.0
		100×2.0
		100×3.0
		150×2.0
		150×3.0
ULTRON AF-HILIC-CD (PLSS)※ ※ PLSS: PEEK-Lined Stainless steel		50×2.0
		100×2.0
		150×2.0
ULTRON AF-HILIC-CD (Two Guard Cartridges)		5×2.0
ULTRON AF-HILIC-CD	5	100×2.0
		100×4.6
		150×2.0
		150×4.6
		250×2.0
		250×4.6
ULTRON AF-HILIC-CD.G		10×4.0
ULTRON AF-HILIC-CD (Two Guard Cartridges)		5×2.0
		10×4.6
Holder for Guard Cartridge (with Coupler)	-	For 5×2.0 mm column
		For 10×4.6 mm column

### ULTRON AF-HILIC-DA

Product name	Particle size (μm)	Column dimensions Length x I.D. (mm)
ULTRON AF-HILIC-DA	5	100×2.0
		100×4.6
		150×2.0
		150×4.6
		250×4.6
ULTRON AF-HILIC-DA (Two Guard Cartridges)		5×2.0
		10×4.6
Holder for Guard Cartridge (with Coupler)	-	For 5×2.0 mm column
		For 10×4.6 mm column



※ Please do not hesitate to contact us for the other dimensions. Please feel free to contact us with questions related to analyses. Column screening services are also available.

Please be aware that specifications and prices are subject to change without prior notification.