


SHINWA EXPRESS

Application

VOL. 245

Analysis of Maleic acid, DL-Malic acid, Malonic acid and Succinic acid using the ULTRON PS-80H



Column: ULTRON PS-80H (10 μ m)
 Column size: 300 mmL x 8.0 mm I.D.
 Mobile phase: HClO₄ aq. (pH 2.1)
 Flow rate: 1.0 mL/min
 Column temp.: 60°C
 Detection: RI

Sample: 1. Maleic acid (2500 mg/L)
 2. DL-Malic acid (5000 mg/L)
 3. Malonic acid (5000 mg/L)
 4. Succinic acid (5000 mg/L)
 Diluent: water
 Injection vol.: 5 μ L

● Features of the ULTRON PS-80H

1. The ULTRON PS-80H columns are HPLC columns packed with a sulfonic acid type polystyrene cation exchange resin designed for organic acid analyses.
2. The columns utilize electrostatic repulsion interactions.
3. The columns display excellent retention reproducibility.
4. The columns are durable due to the use of a mechanically strong polymer gel.



SHINWA CHEMICAL INDUSTRIES LTD.

50-2 Kagekatsu-cho, Fushimi-ku
 Kyoto 612-8307 Japan
 TEL: +81-75-621-2360 FAX: +81-75-602-2660
 E-mail: info@shinwa-cpc.co.jp
 Website: <https://shinwa-cpc.co.jp/en/>

■ Analytical column specifications ■

ULTRON PS-80H / PS-80N / PS-80C / PS-80P

Product name	Particle size (μm)	Column dimensions Length x I.D. (mm)
ULTRON PS-80H	10	300×8.0
		250×2.0
ULTRON PS-80H.G		50×8.0
ULTRON PS-80N		300×8.0
ULTRON PS-80N.L		500×8.0
ULTRON PS-80N.G		50×8.0
ULTRON PS-80C		300×8.0
ULTRON PS-80C.G		50×8.0
ULTRON PS-80P		300×8.0
ULTRON PS-80P.G		50×8.0



※ Please do not hesitate to contact us for the other dimensions.
Please feel free to contact us with questions related to analyses.
Column screening services are also available.

Please be aware that specifications and prices are subject to change without prior notification.